



OMEO KUMAR DAS INSTITUTE OF SOCIAL CHANGE AND DEVELOPMENT

VIP Road, Upper Hengrabari, Guwahati-781036, Assam, India

Phone : 0361-2333064, 2335204 (0), 2335206 (Fax)

e-mail : dkdscd@yahoo.co.in, Web : www.okd.in

Advertisement No. OKDISCD/NIQ/2020-21/01

File No. ISCD/Estt/49A/91

SHORT NOTICE INVITING TENDER

Omeo Kumar Das Institute of Social Change and Development, Guwahati invites sealed quotations from registered Dealers / Suppliers for supply and installation of Group Video Conferencing System with Professional Display. They may quote their best rates (inclusive all taxes) in the specified format given herewith. The quotation superscribed with "Quotation for Group Video Conferencing System with Professional Display" and addressed to "The Director (i/c), OKDISCD, VIP Road, Guwahati - 781 036" should reach the Institute's office on or before 11.01.2021 by 1000 hrs.

Date: 07.01.2021

Sd/-

Director (i/c)




To
The Director (i/c)
OKD Institute of Social Change and Development
VIP Road, Guwahati – 781 036

Sub: Rates for supply and installation of Group Video Conferencing System with Professional Display

Madam,

With reference to the above, please find below our best rates for the following items:

Sl. No	Item	Description	Qty	Rate to be Offered (Inclusive all Taxes)
1	Video Conferencing system	<p>Video System: 1080P, 720P, 540P, 480P, 360P, 240P etc. Sensor: 1/2.7", CMOS, Effective Pixel: 2.07M Scanning Mode: Progressive Lens: f4.7mm ~ 46.3mm, F1.8 ~ F2.8 Optical Zoom: 10x Digital Zoom: 16x Minimal Illumination: 0.5 Lux @ (F1.8, AGC ON) Shutter: 1/30s ~ 1/10000s White Balance: Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Backlight Compensation: Support Digital Noise Reduction: 2D&3D Digital Noise Reduction Horizontal Angle of View: 58.5° ~ 6.5° Vertical Angle of View: 35.1° ~ 3.6° Horizontal Rotation Range: ±170° Vertical Rotation Range: 30° ~ 90° Pan Speed Range: 2.7° ~ 35.7°/s Tilt Speed Range: 2.7° ~ 31.5°/s H & V Flip: Support Image Freeze: Support USB Interface: 1xUSB2.0: Type B female jack Communication Interface: 1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D /Pelco-P</p>	1	
2	Speaker phone with 3 extension microphones	<p>Interface: Control Unit: USB 2.0 High Speed, Bluetooth, NFC (Near Field Communication) Audio Input terminal (stereo RCA pin), Audio Output terminal (stereo RCA pin), External speaker terminal (RCA pin) x 2, Power terminal, Microphone terminal Microphone: Input and output terminals Power consumption (max): 20 W (one connected microphone), 35 W (five connected microphones) Radio interference standard: FCC (Part 15B) Class A, ICES-003 Operating environment: Temperature: 0 to 40°C (32 to 104°F) Humidity: 20 to 85% (no condensation) Control Unit: 1.8 kg (4.0 lbs), Microphone: 0.4 kg (0.9 lbs) Power source: 120 V (60 Hz) Bluetooth specification version: 2.1 + EDR Supported</p>	1	



		<p>profile: HFP (1.6), A2DP Supported Codec: SBC, mSBC Wireless output: Class 2 Maximum communication distance: 10 m (32.8 ft) Compatible devices: NFC-compatible Android devices, versions 4.1, 4.2, 4.3 and 4.4 Voice guidance English, Japanese, Chinese, Korean, French, Spanish, German Accessories Microphone unit: Unidirectional x 3, Speaker unit: Full-range x 1 Maximum volume: 95 dB (0.5 m (1.6 ft)), Frequency bandwidth : For sound pickup: 100 to 20,000 Hz, For playback: 100 to 20,000 Hz Signal processing: Adaptive echo canceller, Noise reduction, Automatic tracking, Automatic gain control, Automatic room EQ, De reverberation, Automatic audio tuning</p> <p>Extension Microphone External interfaces: Input and output terminals Radio interference standard: FCC (Part 15B) Class A, ICES-003 Operating environment Temperature: 0 to 40°C (32 to 104°F), Humidity: 20 to 85% (no condensation) Accessories: Microphone cable (5 m), User's Microphones: Unidirectional x 3 Frequency bandwidth for sound pickup: 100 to 20,000 Hz</p>		
3	Display	<p>Size: 55" Diagonal Resolution: 4K Running Time: 16X7 Hrs Brightness: 350 Cdm Features: Android and inbuilt signage player Terminals: HDMI, DP, USB</p>	1	
4	Mounting, cables and connectors	Required cables and connectors of international standard (Preferably from ATEN/Kramer/Extron/Wbox)		
5	Installation, testing and commissioning	Job		

Date:

(Signature)

Name of the vendor:

Address:

Contact no.:

E-mail:

Documents to be submitted along with the quotation:

- Copy of firm registration
- Copy of PAN
- Copy of GST registration certificate
- Copy of Bid Specific MAF against each product

